

# PARADISE PARK PLAN

## UBAOG MUTUAL SELF-HELP HOUSING PROGRAM UINTAH BASIN

APRIL 2017

INDEX TO DRAWINGS	
DWG	TITLE
A101	MAIN LEVEL FLOOR PLAN
A201	EXTERIOR ELEVATIONS
S101	FOOTING & FOUNDATION PLAN
S102	FLOOR FRAMING PLAN
S103	ROOF PLAN
S301	SECTION DETAILS
E101	MAIN ELECTRICAL PLAN



<b>WARRIOR</b> <small>2863 South 2500 East Vernal, Utah 84078 (435) 828-6272</small> UTAH - COLORADO - WYOMING
<small>CLIENT INFO:</small> UBAOG 330 EAST 100 SOUTH ROOSEVELT, UT 84066  435-722-4518 <small>DRAWN BY:</small> CMM <small>PROJECT MANAGER:</small> CMM <small>CHECKED BY:</small> DEM
<b>PARADISE PARK PLAN MUTUAL SELF-HELP UBAOG - ROOSEVELT UINTAH BASIN</b>
COVER

Door Schedule				
Mark	Size	Description	Count	Notes
1	16'-0" X 8'-0"	16' X 8' Fold-Up Door	1	
2	3'-0" X 6'-8"	36" Decorative Entry Door 1	1	
3	3'-0" X 6'-8"	36" Steel Door	2	
4	2'-4" X 6'-8"	28" Hinged Door - 6 panel	2	
5	2'-6" X 6'-8"	30" Hinged Door - 6 panel	5	
6	2'-0" X 6'-8"	24" Hinged Door - 6 panel	2	
7	4'-0" X 6'-8"	48" Bi-Fold Door	3	
8	1'-6" X 6'-8"	18" Hinged Door - 6 panel	1	
9	4'-0" X 6'-8"	48" Dbl Hinged Door - 6 panel	2	
10	5'-0" X 6'-8"	5' Sliding Glass Door	1	

Window Schedule				
Mark	Size	Description	Count	Notes
1	4'-0" X 4'-0"	4'-0" X 4'-0" Sliding Window	3	
2	5'-0" X 4'-0"	5'-0" X 4'-0" Sliding Window	1	
3	2'-0" X 5'-0"	2'-0" X 5'-0" Hung Window	2	
4	4'-0" X 5'-0"	4'-0" X 5'-0" Picture Window	1	
5	3'-0" X 2'-0"	3'-0" X 2'-0" Sliding Window	1	
6	3'-0" X 3'-0"	3'-0" X 3'-0" Sliding Window	1	
7	3'-0" X 3'-6"	3'-0" X 3'-6" Sliding Window	1	

**CODE REQUIREMENTS:**

- LOTS SHALL BE GRADED TO DRAIN SURFACE WATER AWAY FROM FOUNDATION WALLS. THE GRADE SHALL FALL A MINIMUM OF 6 INCHES WITHIN THE FIRST 10 FEET. (IRC R401.3)
- FIRE STOP ALL CONCEALED SPACES SO NO FREE AIRFLOW EXISTS FROM HORIZONTAL TO VERTICAL AND AT EVERY 10 FEET BOTH HORIZONTAL AND VERTICAL. (IRC R302.11)
- ASSURE PROPER PROTECTION OF ALL PLUMBING AND WIRING. (IRC P2603 & TABLE IRC E3802.1)
- ASSURE PROPER SUPPORT OF ALL DUCT INSTALLATION. (IRC M1601.4.3)
- MAINTAIN PROPER CLEARANCES FROM COMBUSTIBLE MATERIAL AT COMBUSTION EXHAUST VENTS. (AS PER MANUFACTURERS LISTING AND LABELING)
- PROVIDE AN ELECTRICAL OUTLET WITHIN 25 FEET OF THE AIR CONDITIONING UNIT. (IRC E3901.11)
- EXTERIOR COVERING SHALL MEET THE REQUIREMENTS OF (IRC R703)
- FLASH ALL FOUNDATIONS AS REQUIRED FOR STONE AND STUCCO PER MANUFACTURERS REQUIREMENTS. (IRC R703)
- MAKE SURE ALL WATER PIPE IS PROPERLY SUPPORTED BOTH VERTICALLY AND HORIZONTALLY AS PER (IRC TABLE P2605.1)
- FLOOR DRAINS SHALL BE FITTED WITH A TRAP PRIMER OR SHALL BE OF THE DEEP SEAL DESIGN. (IRC P3201.2 EXCEPTION)
- MANUFACTURERS SPECIFICATIONS ARE REQUIRED FOR THE FIREPLACE AT 4-WAY.
- INSULATION DEPTH MARKERS ARE REQUIRED EVERY 300 SQ. FT. MAX (IRC N1101.4.1)
- ROOF COVERINGS SHALL MEET THE REQUIREMENTS OF (IRC R905)
- ROOF SHALL BE VENTILATED AS PER (IRC R806)
- ALL CONSTRUCTION DEBRIS SHALL BE CONTAINED ON SITE AND DISPOSED OF IN AN APPROVED LANDFILL.
- STAIRS HANDRAILS AND GUARDRAILS SHALL MEET THE REQUIREMENTS OF (IRC R311.7) ALL GUARDRAILS TO BE A MINIMUM HEIGHT OF 36" AND HAVE NO NET OPENINGS EXCEEDING 4".
- WINDOWS WITHIN 24 INCHES OF THE VERTICAL EDGES OF DOORS SHALL BE TEMPERED OR SAFETY GLASS. WINDOWS WITHIN A TUB OR SHOWER COMPARTMENT SHALL BE TEMPERED OR SAFETY GLASS. (IRC R308)
- BRICK VENEER SHALL HAVE WALL TIES, FLASHING, WEEP HOLES, REINFORCEMENT AS PER (IRC R703)
- ASSURE ELECTRICAL OUTLET SPACING AS REQUIRED. (IRC E3901)
- ALL BEDROOM OUTLETS SHALL BE ON A COMBINATION TYPE ARC FAULT CIRCUIT BREAKER (IRC E3902).
- TUBS AND SHOWERS WITH TILED WALLS AND WALL PANELS IN SHOWER AREAS SHALL MEET THE REQUIREMENTS OF (IRC R702.4.2). NOTE: THE BACKER BOARD CANNOT BE INSTALLED OVER GREEN BOARD. ALSO NOTE: UNLESS THE BACKER BOARD HAS BEEN EVALUATED AS A WATER PROOF MEMBRANE A MOISTURE BARRIER IS REQUIRED. THE MOISTURE BARRIER MUST BE INSTALLED OVER FRAMING AND MUST BE FREE FROM HOLES AND BREAKS.
- A PROGRAMMABLE THERMOSTAT IS REQUIRED WHERE THE PRIMARY HEATING SYSTEM IS A FORCED AIR FURNACE. (IRC N1103.1.1).
- ALL WASHERS FOR ANCHOR BOLTS SHALL BE 3 INCH BY 3 INCH BY 0.229 MINIMUM (IRC R602.11.1)
- WINDOW SILLS SHALL BE A MINIMUM OF 24 INCHES ABOVE THE FINISHED FLOOR WHERE THE OPENING OF AN OPERABLE WINDOW IS LOCATED MORE THAN 72 INCHES ABOVE THE FINISHED GRADE OR SURFACE BELOW (IRC R612.2)
- WHERE THE DRYER DUCT IS CONCEALED WITHIN THE BUILDING CONSTRUCTION, THE EQUIVALENT LENGTH OF THE DRYER DUCT SHALL BE IDENTIFIED ON A PERMANENT LABEL OR TAG. THE LABEL OR TAG SHALL BE LOCATED WITHIN 6 FEET OF THE DRYER DUCT CONNECTION. (IRC M1502.4.5).
- ALL RECEPTACLES SHALL BE TAMPERPROOF. (IRC E4002.14)
- ALL EXTERIOR RECEPTACLES SHALL BE WEATHERPROOF AND HAVE IN USE WEATHERPROOF COVERS. (IRC E4002.8, E4002.9, E4002.10 AND E4002.14)

**NOTES:**


ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE 2015 I.R.C. AND ALL APPLICABLE LOCAL BUILDING CODES.

GREAT EFFORT HAS BEEN MADE TO VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL DIMENSIONS PRIOR TO STARTING CONSTRUCTION. IT IS ANTICIPATED THAT SOME ELEMENTS MAY NEED TO BE ADJUSTED IN THE FIELD.

ALL EXTERIOR WALLS ARE 2"x6" STUDS @ 16" O.C., WITH FULL DEPTH BLOW-IN INSULATION.

**CONSTRUCTION NOTES:**

- TRUSS SPECIFICATIONS ARE REQUIRED AT 4-WAY INSPECTION.
- ADDRESS MUST BE POSTED DURING ALL PHASES OF CONSTRUCTION.
- PLANS SHALL BE AVAILABLE ON SITE FOR ALL INSPECTIONS.
- ENERGY COMPLIANCE CERTIFICATE MUST BE POSTED ON ELECTRICAL PANEL FOR FINAL INSPECTION. (IRC N1101.9)
- PROVIDE A CONCRETE ENCASED ELECTRODE AVAILABLE FOR USE AS A GROUNDING ELECTRODE FOR THE HOUSE. MUST BE IN PLACE AT FOOTING INSPECTION. (IRC E3608.1)
- SEWER, WATER-LINE AND SHOWER PAN INSPECTIONS REQUIRED.
- WATER LINE FROM METER TO HOUSE SHALL BE 1"(BASED ON 20.8 FIXTURE UNITS @ 49 PSI) TABLE (IRC AP201.1) THIS IS CALCULATED PER THE SUBMITTED PLOT PLAN FOR THE HOUSE.



**WARRIOR**  
 2863 South 2500 East  
 Vernal, Utah 84078  
 (435) 828-6272  
 UTAH - COLORADO - WYOMING

---

CLIENT INFO:  
 UBAOG  
 330 EAST 100 SOUTH  
 ROOSEVELT, UT 84066

435-722-4518  
 DRAWN BY:  
 CMM  
 PROJECT MANAGER:  
 CMM  
 CHECKED BY:  
 DEM

---


**PARADISE PARK PLAN**  
**MUTUAL SELF-HELP**  
**UBAOG - ROOSEVELT**  
**UINTAH BASIN**

---

**MAIN LEVEL FLOOR PLAN**

---


**A101**



**BACK ELEVATION**




**RIGHT ELEVATION**



**LEFT ELEVATION**

ASPHALT/FIBERGLASS COMP. SHINGLES  
w/ 15# UNDERLAYMENT, PROVIDE ICE &  
WATER SHIELD @ EDGES AND VALLEYS



**FRONT ELEVATION**

A EXTERIOR ELEVATION  
A201 SCALE: 1/4" = 1'-0"

**WARRIOR**

2863 South 2500 East  
Vernal, Utah 84078  
(435) 828-6272

UTAH - COLORADO - WYOMING


CLIENT INFO:  
UBAOG  
330 EAST 100 SOUTH  
ROOSEVELT, UT 84066

435-722-4518  
DRAWN BY:  
CMM  
PROJECT MANAGER:  
CMM  
CHECKED BY:  
DEM

**PARADISE PARK PLAN**  
**MUTUAL SELF-HELP**  
**UBAOG - ROOSEVELT**  
**UINTAH BASIN**

EXTERIOR  
ELEVATIONS

**A201**



**A** FOOTING & FOUNDATION PLAN  
**S101** SCALE: 1/4" = 1'-0"


FOOTING &  
 FOUNDATION  
 PLAN

**S101**

**PARADISE PARK PLAN**  
**MUTUAL SELF-HELP**  
 UBAOG - ROOSEVELT  
 UINTAH BASIN


CLIENT INFO:  
 UBAOG  
 330 EAST 100 SOUTH  
 ROOSEVELT, UT 84066  
 435-722-4518  
 DRAWN BY:  
 CMM  
 PROJECT MANAGER:  
 CMM  
 CHECKED BY:  
 DEM

**WARRIOR**  
 2863 South 2500 East  
 Vernal, Utah 84078  
 (435) 828-6272  
 UTAH - COLORADO - WYOMING



**A FLOOR FRAMING PLAN**  
 S102 SCALE: 1/4" = 1'-0"

<b>WARRIOR</b> <small>2863 South 2500 East        Vernal, Utah 84078        (435) 828-6272</small> UTAH - COLORADO - WYOMING
<small>CLIENT INFO:</small> UBAOG 330 EAST 100 SOUTH ROOSEVELT, UT 84066  435-722-4518 <small>DRAWN BY:</small> CMM <small>PROJECT MANAGER:</small> CMM <small>CHECKED BY:</small> DEM
<b>PARADISE PARK PLAN</b> <b>MUTUAL SELF-HELP</b> UBAOG - ROOSEVELT UINTAH BASIN
<b>FLOOR FRAMING PLAN</b>
<b>S102</b>



**NOTES:**  
 ROOF PLAN IS SCHEMATIC ONLY.  
 ACTUAL LAYOUT TO BE PROVIDED BY  
 TRUSS MANUFACTURER.  
 TRUSSES SHALL BE ENGINEERED BY  
 MANUFACTURER

**DESIGN LOADS:**  
 DEAD LOAD: 15 PSF  
 LIVE LOAD: 20 PSF  
 SNOW LOAD: 30 PSF (VERIFY)

A ROOF PLAN  
 S103 SCALE: 1/4" = 1'-0"

**WARRIOR**

2863 South 2500 East  
 Vernal, Utah 84078  
 (435) 828-6272

UTAH - COLORADO - WYOMING





CLIENT INFO:  
 UBAOG  
 330 EAST 100 SOUTH  
 ROOSEVELT, UT 84066

435-722-4518  
 DRAWN BY:  
 CMM  
 PROJECT MANAGER:  
 CMM  
 CHECKED BY:  
 DEM

**PARADISE PARK PLAN  
 MUTUAL SELF-HELP  
 UBAOG - ROOSEVELT  
 UINTAH BASIN**

ROOF  
 PLAN

**S103**



**A SECTIONS**  
S301 SCALE: 1/4" = 1'-0"

**WARRIOR**

2863 South 2500 East  
Vernal, Utah 84078  
(435) 828-6272

UTAH - COLORADO - WYOMING


CLIENT INFO:  
UBAOG  
330 EAST 100 SOUTH  
ROOSEVELT, UT 84066

435-722-4518  
DRAWN BY:  
CMM  
PROJECT MANAGER:  
CMM  
CHECKED BY:  
DEM

**PARADISE PARK PLAN**  
**MUTUAL SELF-HELP**  
**UBAOG - ROOSEVELT**  
**UINTAH BASIN**

**SECTION DETAILS**

**S301**



### Electrical Legend

Symbol	Description
	120 VOLT OULET
	120 VOLT OUTLET GFI
	220 VOLT OUTLET
	SWITCH
	EXHAUST FAN
	SMOKE DETECTOR
	RECESSED CEILING LIGHT
	TYP. LIGHT FIXTURES PER OWNER AS SHOWN

A NOTES & SCHEDULES  
 A501 SCALE: 1/4" = 1'-0"

MAIN FLOOR  
 ELECTRICAL  
 PLAN

E101

**PARADISE PARK PLAN**  
**MUTUAL SELF-HELP**  
 UBAOG - ROOSEVELT  
 UINTAH BASIN

435-722-4518  
 DRAWN BY:  
 CMM  
 PROJECT MANAGER:  
 CMM  
 CHECKED BY:  
 DEM

CLIENT INFO:  
 UBAOG  
 330 EAST 100 SOUTH  
 ROOSEVELT, UT 84066

**WARRIOR**  
 2863 South 2500 East  
 Vernal, Utah 84078  
 (435) 828-6272  
 UTAH - COLORADO - WYOMING